FIG 1

Data with no Jitter



FIG 2

Data with Jitter



FIG 3



FIG 4



50



FIG 5
~~Figure 1-1~~: *High Level Block Diagram of Edge Based Receiver.*

09752813.122900



Figure ~~1-2~~ 6: Edge Buffer Block Diagram.

09752813.122200



Figure 7: Timing Diagrams for the Edge Pipelines.

09752813 .122900

52



Figure ~~1-5~~ 8: Edge Processing Block Diagram.



Figure 1-6: Synchronizer Timing Diagram.



Figure 1-7: Phase Picking Mechanism Block Diagram.

DOCKET.COM

FIG 11


START
DETECTING EDGES IN DATA STREAM
131
TRACKING TRANSMITTED CLOCK WITH MULTIPLE LOCAL CLOCK PHASES
132
CALCULATING MOVING AVERAGE OF EDGES
133
DETERMINING WHETHER EDGE ARRIVED EARLY OR LATE RELATIVE TO EXPECTED ARRIVAL TIME
134
USING DETERMINATION WHETHER EDGE ARRIVED EARLY OR LATE IN RECEIVER DECISION PROCESS
135
STOP

130

FIG 12a



FIG 12b



FIG 12c



FIG 12d



09752813.122900



FIG. 13

09752813.122900



FIG 14

Signals	A	A#	B	B#	A + B	A# + B#	High Out
Actual Volt.	1.0V	0.5V	0.25V	-0.25V	1.25V	0.25V	+
			-0.25V	0.25V	0.75V	0.75V	-
			0.05V	-0.05V	1.05V	0.45V	+
			-0.05V	0.05V	0.95V	0.55V	-
			0V	0V	1.0V	0.5V	tie
	0.5v	1.0v	0.25V	-0.25V	0.75V	0.75V	+
			-0.25V	0.25V	0.25V	1.25V	-
			0.05V	-0.05V	0.55V	0.95V	+
			-0.05V	0.05V	0.45V	1.05V	-
			0V	0V	0.5V	1.0V	tie

FIG 15



FIG 16